



6010

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent of

WANG et al

Atty. Ref.: 839-1016

Patent No. 6,608,409

Issued: August 19, 2003

For: HIGH-TEMPERATURE SUPER-CONDUCTING ROTOR
HAVING A VACUUM VESSEL AND
ELECTROMAGNETIC SHIELD AND METHOD FOR
ASSEMBLY

* * * * *

August 27, 2003

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Certificate

SEP 03 2003

of Correction

Sir:

REQUEST FOR A CERTIFICATE OF CORRECTION

The patentee in the above-identified patent hereby requests that the Patent and Trademark Office issue an official Certificate of Correction pursuant to 37 C.F.R. § 1.322 for the following errors made by the Patent Office.

The following claims were amended in the Amendment filed by the applicant on January 21, 2003. All claim amendments were approved in the Notice of Allowance of May 7, 2003. however, the claims as amended do not appear in the patent grant. The claims as amended on January 21, 2003 are as follows:

1. In a synchronous machine a rotor comprising:

a rotor core;

SEP 03 2003

a super-conducting coil mounted on said rotor core and said coil having at least one coil side section extending along a side of the rotor core and radially outward of the side of the rotor core;

a vacuum housing straddling the at least one coil side section, wherein the vacuum housing further comprises a top plate and a pair of opposite sidewalls such that the at least one coil side section is enclosed on three sides by the vacuum housing, and further the sidewalls are in sealing engagement with the side of the rotor core, and a conductive shield extending over said vacuum housing and coil side sections.

2. In a rotor as in claim 1 wherein said vacuum housing is a channel housing extending longitudinally along said side of said rotor core, wherein said side is a planar section of the core and said coil side section and vacuum housing extend radially outward of said planar section.

6. In a rotor as in claim 1 further comprising a planar surface extending longitudinally across the rotor core, wherein the at least one of coil side section is adjacent the planar surface and extends radially outward of said planar surface.

8. In a rotor as in claim 1 further comprising a plurality of braces buttressing the sidewalls of the vacuum housing and conductive shield.

9. A rotor comprising:

a rotor core having an axis;

an end shaft extending axially from an end of said core, wherein said end shaft has

a slot adjacent the core end;

a super-conducting rotor coil having at least one coil side parallel to the core axis
and at least one coil end transverse to said core axis, wherein said coil end extends
through said slot in the end shaft and said coil side extends radially outward of
said rotor core;

a vacuum housing over said coil side and seal with said slot to define a vacuum
region around said coil, wherein said vacuum housing has a rectangular cross-
section and further comprises a top plate and a pair of opposite sidewalls such that
the coil side is enclosed on a plurality of sides by the vacuum housing, and further
the sidewalls are in sealing engagement with the rotor core.

11. A rotor as in claim 9 wherein said vacuum housing is sealed to said rotor core
on both sides of said coil side.

12. A rotor as in claim 11 wherein each side wall is sealed to a surface of the rotor
core along an entire length of the rotor core.

15. A rotor as in claim 9 further comprising a plurality of braces buttressing said
sidewalls of the vacuum housing and attached to said rotor core.

16. A rotor as in claim 15 further comprising an electromagnetic shield around said braces.

17. A rotor comprising:

a rotor core having an axis;

a pair of end shafts extending axially from opposite ends of said core, wherein said end shafts each have a slot adjacent the core end;

a super-conducting rotor coil having at least one coil side section parallel to the core axis and adjacent opposite sides of said core, and said coil having coil end sections transverse to said core axis and adjacent the ends of said core, wherein said coil end sections each extend through one of said slots in the end shafts and said coil side section extends radially outward of said rotor core;

a vacuum housing over each said coil side sections and having ends each being sealed to one of slots, wherein said vacuum housing further comprises a top plate and a pair of opposite sidewalls such that the coil side is enclosed on a plurality of sides by the vacuum housing, and further the opposite sidewalls are in sealing engagement with the rotor core, and

a vacuum region around said coil defined by the slot in said pair of end shafts and the vacuum housing over each of said coil side sections.

18. A rotor as in claim 17 further comprising a conductive shield over said coil side sections and overlapping with said end shafts, such that the shield is sealed to the end shafts.

20. A rotor as in claim 18 wherein said shield is formed partially by a top portion said vacuum housing.

The above amended claims should have been in the patent grant.

Since the error arose on the part of the Patent and Trademark Office, no fee is believed necessary for securing issuance of the Certificate.

Attached hereto is a draft Official Certificate of Correction for use by the Patent and Trademark Office correcting the above-identified matter.


The Commissioner is hereby authorized to charge any deficiency in the fee(s) filed, or asserted to be filed, or which should have been filed herewith (or with any paper hereafter filed in this application by this firm) to our **Account No. 14-1140**. A duplicate copy of this sheet is attached.

WANG et al
Patent No. 6,608,409

Respectfully submitted,

NIXON & VANDERHYE P.C.

By: _____


Jeffrey H. Nelson
Reg. No. 30,481

JHN:imm
1100 North Glebe Road, 8th Floor
Arlington, VA 22201-4714
Telephone: (703) 816-4000
Facsimile: (703) 816-4100

Staple
Here
Only!

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 6,608,409
DATED : August 19, 2003
INVENTOR(S) : WANG et al

It is certified that error appears in the above-identified patent and that said letters patent is hereby corrected as shown below:

1. In a synchronous machine a rotor comprising:

a rotor core;

a super-conducting coil mounted on said rotor core and said coil having at least one coil side section extending along a side of the rotor core and radially outward of the side of the rotor core;

a vacuum housing straddling the at least one coil side section, wherein the vacuum housing further comprises a top plate and a pair of opposite sidewalls such that the at least one coil side section is enclosed on three sides by the vacuum housing, and further the sidewalls are in sealing engagement with the side of the rotor core, and

a conductive shield extending over said vacuum housing and coil side sections.

MAILING ADDRESS OF SENDER:

Jeffrey H. Nelson
NIXON & VANDERHYE P.C.
1100 North Glebe Road, 8th Floor
Arlington, Virginia 22201

PATENT NO.

6,608,409

No. of add.
@ 50¢ per page

SEP 03 2003

US

Staple
Here
Only!

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 6,608,409
DATED : August 19, 2003
INVENTOR(S) : WANG et al

It is certified that error appears in the above-identified patent and that said letters patent is hereby corrected as shown below:

2. In a rotor as in claim 1 wherein said vacuum housing is a channel housing extending longitudinally along said side of said rotor core, wherein said side is a planar section of the core and said coil side section and vacuum housing extend radially outward of said planar section.
6. In a rotor as in claim 1 further comprising a planar surface extending longitudinally across the rotor core, wherein the at least one of coil side section is adjacent the planar surface and extends radially outward of said planar surface.
8. In a rotor as in claim 1 further comprising a plurality of braces buttressing the sidewalls of the vacuum housing and conductive shield.

MAILING ADDRESS OF SENDER:

Jeffrey H. Nelson
NIXON & VANDERHYE P.C.
1100 North Glebe Road, 8th Floor
Arlington, Virginia 22201

PATENT NO. 6,608,409

No. of add.
\$ 50.00 per page

Staple
Here
Only!

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 6,608,409
DATED : August 19, 2003
INVENTOR(S) : WANG et al

It is certified that error appears in the above-identified patent and that said letters patent is hereby corrected as shown below:

9. A rotor comprising:

a rotor core having an axis;

an end shaft extending axially from an end of said core, wherein said end shaft has a slot adjacent the core end;

a super-conducting rotor coil having at least one coil side parallel to the core axis and at least one coil end transverse to said core axis, wherein said coil end extends through said slot in the end shaft and said coil side extends radially outward of said rotor core;

a vacuum housing over said coil side and seal with said slot to define a vacuum region around said coil, wherein said vacuum housing has a rectangular cross-section and further comprises a top plate and a pair of opposite sidewalls such that the coil side is enclosed on a plurality of sides by the vacuum housing, and further the sidewalls are in sealing engagement with the rotor core.

11. A rotor as in claim 9 wherein said vacuum housing is sealed to said rotor core on both sides of said coil side.

MAILING ADDRESS OF SENDER:

Jeffrey H. Nelson
NIXON & VANDERHYE P.C.
1100 North Glebe Road, 8th Floor
Arlington, Virginia 22201

PATENT NO.

6,608,409

No. of add'l
@ 50¢ per page

SEP 03 2003

Staple
Here
Only!

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 6,608,409
DATED : August 19, 2003
INVENTOR(S) : WANG et al

It is certified that error appears in the above-identified patent and that said letters patent is hereby corrected as shown below:

12. A rotor as in claim 11 wherein each side wall is sealed to a surface of the rotor core along an entire length of the rotor core.

15. A rotor as in claim 9 further comprising a plurality of braces buttressing said sidewalls of the vacuum housing and attached to said rotor core.

16. A rotor as in claim 15 further comprising an electromagnetic shield around said braces.

MAILING ADDRESS OF SENDER:

Jeffry H. Nelson
NIXON & VANDERHYE P.C.
1100 North Glebe Road, 8th Floor
Arlington, Virginia 22201

PATENT NO. 6,608,409

No. of addi
© 50¢ per page

Staple
Here
Only!

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 6,608,409
DATED : August 19, 2003
INVENTOR(S) : WANG et al

It is certified that error appears in the above-identified patent and that said letters patent is hereby corrected as shown below:

17. A rotor comprising:

a rotor core having an axis;

a pair of end shafts extending axially from opposite ends of said core, wherein said end shafts each have a slot adjacent the core end;

a super-conducting rotor coil having at least one coil side section parallel to the core axis and adjacent opposite sides of said core, and said coil having coil end sections transverse to said core axis and adjacent the ends of said core, wherein said coil end sections each extend through one of said slots in the end shafts and said coil side section extends radially outward of said rotor core;

a vacuum housing over each said coil side sections and having ends each being sealed to one of slots, wherein said vacuum housing further comprises a top plate and a pair of opposite sidewalls such that the coil side is enclosed on a plurality of sides by the vacuum housing, and further the opposite sidewalls are in sealing engagement with the rotor core, and

a vacuum region around said coil defined by the slot in said pair of end shafts and the vacuum housing over each of said coil side sections.

MAILING ADDRESS OF SENDER:

Jeffrey H. Nelson
NIXON & VANDERHYE P.C.
1100 North Glebe Road, 8th Floor
Arlington, Virginia 22201

PATENT NO. 6,608,409

No. of addi-
@ 50¢ per page

SEP 03 2003

24

Staple
Here
Only!

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 6,608,409
DATED : August 19, 2003
INVENTOR(S) : WANG et al

It is certified that error appears in the above-identified patent and that said letters patent is hereby corrected as shown below:

18. A rotor as in claim 17 further comprising a conductive shield over said coil side sections and overlapping with said end shafts, such that the shield is sealed to the end shafts.

20. A rotor as in claim 18 wherein said shield is formed partially by a top portion said vacuum housing.

MAILING ADDRESS OF SENDER:

Jeffrey H. Nelson
NIXON & VANDERHYE P.C.
1100 North Glebe Road, 8th Floor
Arlington, Virginia 22201

PATENT NO.

6,608,409

No. of addi
● 50¢ per page